

关于我们
产品目录

**About Us
Products**

关于我们

布龙斯包装坐落于国际武打巨星李小龙的故乡中国广东
佛山均安镇。

自2009年，布龙斯技术团队已致力于包装机械制造和销售，
经验丰富，技术扎实，并于2013年创立布龙斯包装机械有限
公司，致力为国内外客户提供一站式的自动化包装整线专案。

我们专注于给袋型包装机的研发和制造，此机结构紧凑，技
术创新，操作简易，用于各类预制袋的包装应用，具备一机支
持多种袋型的特点，特别适用于食品行业的包装应用。

我们的立式系列包装机，结构创新，技术成熟稳定，性价比高，
适合食品，工业等领域各类膜成型袋的包装应用。

About Us

Bucepack is located at Junan Town of Foshan City in south
China. The Hometown of Bruce Lee. The international and
famous super star of Chinese Kongfu.

The bucepack team has been devoted in manufacturing and
selling package machine Since 2009, with those rich experiences
and smart concepts in mind all along, we started Bucepack
package machinery co., ltd at 2013 finally.

With typical actions to do pick, fill and seal via such a compact
body only. Our DoyBag Packer is full with flexible and innovative
in its blood, which make sure you can get a best solution from us.

Bucepack
布龙斯包装机械 *idea for packaging*

布龙斯机械

简单，直接，期待与你共创美好未来

Bucepack

An simple and concentrated company;
Your long term partner today and future

Contact:

Mob: +86 133 9222 3298(Domestic国内)

+86 133 8024 4450(Oversea海外)

Tel: +86 757 2551 2225

Fax: +86 757 2551 2226

brucepacksales@gmail.com

www.bucepack.com.cn

佛山市布龙斯包装机械有限公司

地址：广东省佛山市顺德区均安镇百安南路60号

邮编：528329

Bucepack Package Machinery Co.,Ltd.

Address: No.60 South Baian Road, Junan
Town Shunde District Foshan City Guangdong
Province, China.
Postcode: 528329



包装范围

 颗粒，粉末，液体，
咖啡，糖果，宠物粮等等
食品&非食品

Handle Range


 Granule, Powder, Liquid,
Coffee Bean, Candy, Petfood etc
Food&Non-Food

机器特性

 操作调节简易&维修成本低
适应多种尺寸的袋子
无袋不下料
安全门
SS304机身和接触部件

Technical Feature

 Easy Operating&Adjustable
Low Maintenance Cost
Multi Bag Format
No Bag No Dump
Interlock
SS304 Machine Frame&Contact Parts

Model: DB-300

选配装置

 SMC气缸
打码机/喷码机
整理装置
保护夹
充/抽气系统
开拉链系统

Option Device

 SMC Pneumatic Component
Dater Printer/Ink-printer
Product Settle
Grip Seal
Gas Flush/Vacuum
Zip Opener

袋型

 三边封
自立袋
拉链袋

Bag Type

 3 Side Seal Bag
Stand-up Bag
Ziplock

技术参数/Technical Parameters

速度/Speed	5-15包/分	5-15Bags/Min
袋尺寸/Bag Size	100mm≤宽≤300mm 100mm≤长≤300mm	100mm≤Width≤300mm 100mm≤Length≤300mm
电源/Power Supply	220V, 50Hz/60Hz, 单相, 1.5kw	220V, 50Hz/60Hz, Single Phase, 1.5kw
气动源/Air	0.5立方米/分, 0.65兆帕	0.5m³/min, 0.65Mpa
机身尺寸/Machine Dimension	长:1750 X 宽:510 X 高:1300mm	L:1750 X W:510 X H:1300mm
电气配置/Electronic	日本三菱PLC/Mitsubishi PLC 日本欧姆龙PID温控 台湾Delta彩色触屏	Mitsubishi PLC Omron PID Temperature Controller Delta Colorful Panel from Taiwan
气动配置/Pneumatic	台湾Air Tac气缸全套 瑞典PIAB真空发生器	Pneumatics Component Airtac from Taiwan PIAB Vacuum Generator from Sweden

包装范围

 颗粒，粉末，液体，
咖啡，糖果，宠物粮等等
食品&非食品

Handle Range

 Granule, Powder, Liquid,
Coffee Bean, Candy, Petfood etc
Food&Non-Food

机器特性

 操作调节简易&维修成本低
适应多种尺寸的袋子
无袋不下料
安全门
SS304机身和接触部件

Technical Feature

 Easy Operating&Adjustable
Low Maintenance Cost
Multi Bag Format
No Bag No Dump
Interlock
SS304 Machine Frame&Contact Parts

Model: DB-430

选配装置

 SMC气缸
打码机/喷码机
整理装置
保护夹
充/抽气系统
开拉链系统
插角袋系统

Option Device

 SMC Pneumatic Component
Dater Printer/Ink-printer
Product Settle
Grip Seal
Gas Flush/Vacuum
Zip Opener
Gusset Device

Special For Ziplock Bag
袋型

 三边封
自立袋
拉链袋
插角袋

Bag Type

 3 Side Seal Bag
Stand-up Bag
Ziplock
Gusset Bag

技术参数/Technical Parameters

速度/Speed	5-15包/分	5-15Bags/Min
袋尺寸/Bag Size	100mm≤宽≤300mm 100mm≤长≤430mm	100mm≤Width≤300mm 100mm≤Length≤430mm
电源/Power Supply	220V, 50Hz/60Hz, 单相, 1.5kw	220V, 50Hz/60Hz, Single Phase, 1.5kw
气动源/Air	0.5立方米/分, 0.65兆帕	0.5m³/min, 0.65Mpa
机身尺寸/Machine Dimension	长:1750 X 宽:510 X 高:1650mm	L:1750 X W:510 X H:1650mm
电气配置/Electronic	日本三菱PLC 日本欧姆龙PID温控 台湾Delta彩色触屏	Mitsubishi PLC Omron PID Temperature Controller Delta Colorful Panel from Taiwan
气动配置/Pneumatic	台湾Air Tac气缸全套 瑞典PIAB真空发生器	Pneumatics Component Airtac from Taiwan PIAB Vacuum Generator from Sweden

包装范围

 颗粒，粉末，液体，
咖啡，糖果，宠物粮等等
食品&非食品

Handle Range

 Granule, Powder, Liquid,
Coffee Bean, Candy, Petfood etc
Food&Non-Food

机器特性

 操作调节简易&维修成本低
适应多种尺寸的袋子
无袋不下料
安全门
SS304机身和接触部件

Technical Feature

 Easy Operating&Adjustable
Low Maintenance Cost
Multi Bag Format
No Bag No Dump
Interlock
SS304 Machine Frame&Contact Parts

Model: DB-Duplex
High-speed

选配置

 SMC气缸
打码机/喷码机
整理装置
保护夹
充/抽气系统

Option Device

 SMC Pneumatic Component
Dater Printer/Ink-printer
Product Settle
Grip Seal
Gas Flush/Vacuum

袋型

 三边封
自立袋

Bag Type

 3 Side Seal Bag
Stand-up Bag

技术参数/Technical Parameters

速度/Speed	10-30包/分	10-30Bags/Min
袋尺寸/Bag Size	100mm≤宽≤200mm 100mm≤长≤300mm	100mm≤Width≤200mm 100mm≤Length≤300mm
电源/Power Supply	220V, 50Hz/60Hz, 单相, 1.5kw	220V, 50Hz/60Hz, Single Phase, 1.5kw
气动源/Air	0.5立方米/分, 0.65兆帕	0.5m³/min, 0.65Mpa
机身尺寸/Machine Dimension	长:1630 X 宽:750 X 高:1450mm	L:1630 X W:750 X H:1450mm
电气配置/Electronic	日本三菱PLC 日本欧姆龙PID温控 台湾Delta彩色触屏	Mitsubishi PLC Omron PID Temperature Controller Delta Colorful Panel from Taiwan
气动配置/Pneumatic	台湾Air Tac气缸全套 瑞典PIAB真空发生器	Pneumatics Component Airtac from Taiwan PIAB Vacuum Generator from Sweden

Vertical Packing Machine 立式包装机系列
应用范围

适合包装各种固体松散物料、粉末物料、液体或膏状物料。如膨化食品、干果、砂糖、盐、醋、饮料、调味酱、小五金件等

Apprication

Loose solid material, such as puffy food, shrimp roll, peanut, popcorn, cornmeal, seed, sugar and salt etc. which shape is roll, slice and granule

机器特性

PLC控制, 触摸屏显示
 伺服控制横封装置动作
 伺服控制拉膜装置动作
 热打码机与拉膜同步动作
 快速更换成型器
 光电控制色点准确切断
 不锈钢机身

Technical Feature

PLC controller with touch screen interface
 Servo-driven end seal jaws
 Servo-driven film transport
 Hot printer and film feeding system synchronous
 Quickly changing one-piece bag former
 Eye mark sensor for film tracking
 Stainless steel frame


Model: mini-620

单伺服系统 **Single Servo Motor**

Model: mini-620D

双伺服系统 **Dual Servo Motor**

精简设计, 整机高度少, 袋宽范围大
Compact and Operator Friendly Design
选配装置

充气/氮装置
 插角装置
 排气装置
 打孔装置
 易撕口装置
 防夹料装置
 安全装置
 袋支撑装置
 PE封合装置
 抽真空装置
 拍底装置
 除静电装置
 四边压线装置
 纠偏装置
 特殊封口

Option Device

Air flushing system/ Nitrogen gas flushing
 Gusset device
 Air expeller
 Hole punch device
 Tear notch device
 Material stopper
 Safety device
 Bag support
 PE sealing system
 Vacuum device
 Flip device
 Static eliminator
 4 lines folding device
 Film tracking device
 Special sealing jaws

可选充填系统

螺旋充填机
 量杯充填机
 液体计量泵
 线性秤
 组合秤

Filling Systems

Auger fillers
 Cup fillers
 Liquid Pump
 Linear scales
 Combination weighers

包装材料

单层PE膜
 多层可热封复合膜

Bag Type

Single-layer PE
 Laminated film

制袋类型

标准枕式袋
 冲孔袋
 插角袋
 平底袋
 连包袋

Bag Type

Stand pillow bag
 Bag with hole
 Gusset bag
 Square bottom bag
 Chain bag

技术参数/Technical Parameters

型号/Model	mini-620	mini-620D
适合膜宽/Film width	Max. 620mm	
制袋宽度/Bag width	70-300mm	
制袋长度/Bag length	50-300mm	
制袋速度/Packing speed	Max.60Bags/Min	Max.100Bags/Min
压缩空气/Air requests	0.4m³/min, 0.6Mpa	0.2m³/min, 0.6Mpa
电源要求/Power supply	220V, 50HZ, 3Kw	220V, 50HZ, 3.5W
外形尺寸/Outer dimension	1310x1130x1300	1310x1130x1300

Vertical Packing Machine 立式包装机系列

应用范围

适合包装各种固体松散物料、粉末物料、液体或膏状物料。如膨化食品、干果、砂糖、盐、醋、饮料、调味酱、小五金件等

Apprication

Loose solid material, such as puffy food, shrimp roll, peanut, popcorn, cornmeal, seed, sugar and salt etc. which shape is roll, slice and granule

机器特性

PLC控制，触摸屏显示
伺服控制横封装置动作
伺服控制拉膜装置动作
热打码机与拉膜同步动作
快速更换成型器
光电控制色点准确切断
不锈钢机身

Technical Feature

PLC controller with touch screen interface
Servo-driven end seal jaws
Servo-driven film transport
Hot printer and film feeding system synchronous
Quickly changing one-piece bag former
Eye mark sensor for film tracking
Stainless steel frame



**Model: BP-400D
BP-500D
BP-620D**

(D: Dual Servo Motor 双伺服系统)

选配置

充气/氮装置
插角装置
排气装置
打孔装置
易撕口装置
防夹料装置
安全装置
袋支撑装置
PE封合装置
抽真空装置
拍底装置
除静电装置
四边压线装置
纠偏装置
特殊封口

Option Device

Air flushing system/ Nitrogen gas flushing
Gusset device
Air expeller
Hole punch device
Tear notch device
Material stopper
Safety device
Bag support
PE sealing system
Vacuum device
Flip device
Static eliminator
4 lines folding device
Film tracking device
Special sealing jaws

可选充填系统

螺旋充填机
量杯充填机
液体计量泵
线性秤
组合秤

Filling Systems

Auger fillers
Cup fillers
Liquid Pump
Linear scales
Combination weighers

包装材料

单层PE膜
多层可热封复合膜

Bag Type

Single-layer PE
Laminated film

制袋类型

标准枕式袋
冲孔袋
插角袋
方底袋
连包袋

Bag Type

Stand pillow bag
Bag with hole
Gusset bag
Square bottom bag
Chain bag

技术参数/Technical Parameters

型号/Model	BP-400D	BP-500D	BP-620D
适合膜宽/Film width	140-400mm	180-500mm	220-620mm
制袋宽度/Bag width	60-190mm	80-240mm	100-300mm
制袋长度/Bag length	50-230mm	50-300mm	50-380mm
制袋速度/Packing speed	Max. 100Bags/Min	Max. 100Bags/Min	Max. 100Bags/Min
压缩空气/Air requests	0.2m³/min, 0.6Mpa	0.2m³/min, 0.6Mpa	0.2m³/min, 0.6Mpa
电源要求/Power supply	220V, 50HZ, 3.5Kw	220V, 50HZ, 4Kw	220V, 50HZ, 4.5Kw
外形尺寸/Outer dimension	1300x960x1150mm	1550x1160x1480mm	1600x1260x1680mm

Vertical Packing Machine 立式包装机系列
应用范围

适合包装各种固体松散物料、粉末物料、液体或膏状物料。如膨化食品、干果、砂糖、盐、醋、饮料、调味酱、小五金件等

Apprication

Loose solid material, such as puffy food, shrimp roll, peanut, popcorn, cornmeal, seed, sugar and salt etc. which shape is roll, slice and granule

机器特性

PLC控制，触摸屏显示
伺服控制拉膜装置动作
打码机与放膜装置同步动作
快速更换成型器
光电控制准确切断
不锈钢机身

Technical Feature

PLC controller with touch screen interface
Servo-driven film transport
Hot printer and film feeding system synchronous
Quickly changing one-piece bag former
Eye mark sensor for film tracking
Stainless steel frame



**Model: BP-400
BP-500
BP-620
BP-800**

(Single Servo Motor 单伺服系统)

选配装置

充气/氮装置
插角装置
排气装置
打孔装置
易撕口装置
防夹料装置
安全装置
袋支撑装置
PE封合装置
抽真空装置
拍底装置
除静电装置
四边压线装置
纠偏装置
特殊封口

Option Device

Air flushing system/ Nitrogen gas flushing
Gusset device
Air expeller
Hole punch device
Tear notch device
Material stopper
Safety device
Bag support
PE sealing system
Vacuum device
Flip device
Static eliminator
4 lines folding device
Film tracking device
Special sealing jaws

可选充填系统

螺旋充填机
量杯充填机
液体计量泵
线性秤
组合秤

Filling Systems

Auger fillers
Cup fillers
Liquid Pump
Linear scales
Combination weighers

包装材料

单层PE膜
多层可热封复合膜

Bag Type

Single-layer PE
Laminated film

制袋类型

标准枕式袋
冲孔袋
插角袋
方底袋
连包袋

Bag Type

Stand pillow bag
Bag with hole
Gusset bag
Square bottom bag
Chain bag

技术参数/Technical Parameters

型号/Model	BP-400	BP-500	BP-620	BP-800
适合膜宽/Film width	140-400mm	180-500mm	220-620mm	340-800mm
制袋宽度/Bag width	60-190mm	80-240mm	100-300mm	160-385mm
制袋长度/Bag length	50-230mm	100-300mm	100-380mm	100-480mm
制袋速度/Packing speed	15-60Bags/Min	15-60Bags/Min	15-60Bags/Min	10-30Bags/Min
压缩空气/Air requests	0.3m³/min, 0.6Mpa	0.36m³/min, 0.6Mpa	0.4m³/min, 0.6Mpa	0.7m³/min, 0.6Mpa
电源要求/Power supply	220V, 50HZ, 3 Kw	220V, 50HZ, 3 Kw	220V, 50HZ, 4 Kw	220V, 50HZ, 4.5 Kw
外形尺寸/Outer dimension	1300x960x1150mm	1550x1160x1480mm	1600x1260x1680mm	1600x1500x2050mm